

Plumbing and Heating Valves

NIBCO®



QT74X

Code#	Description	Size	Mfg#	Box Qty
-------	-------------	------	------	---------

QT74X Quarter-Turn Boiler Drain

- Cup or MIP Threads to Hose
- NSF/ANSI 61-9 compliant
- Sizes - 1/2", 3/4"

26-6752	Quarter-Turn Boiler Drain	1/2	QT74X	20
---------	---------------------------	-----	-------	----



QT763IX

QT763IX Quarter-Turn Angle Sillcock

- 1/2 Cup or 3/4 Ftg. to Hose
- NSF/ANSI 61-9 compliant
- Sizes - 1/2", 3/4"

26-6792	Quarter-Turn Angle Sillcock	1/2	QT763IX	20
---------	-----------------------------	-----	---------	----



76-CL

76-CL Stop and Waste Valve

- FIP x FIP
- 125 lb. CWP to 100 ° F Maximum Temperature 180 ° F CSA B125 Approved and IAPMO Listed
- Size - 1/2", 3/4"

26-6771	Stop-Waste Valve FIP	3/4	76-CL	10
---------	----------------------	-----	-------	----



725-CL

725-CL Stop Valve

- Cup x Cup
- 125 lb. CWP to 100 ° F Maximum Temperature 180 ° F CSA B125 Approved and IAPMO Listed
- Size - 1/2", 3/4"

26-6780	Stop Valve COP	1/2	725CL	10
26-6781	Stop Valve COP	3/4	725CL	10



T-480



T-000-D



Sill Cock

Code#	Description	Size	Mfg#	Box Qty
-------	-------------	------	------	---------

T-480 Class 125 Bronze Ring Check® Valve

- Inline Lift Type - Resilient Discs - Spring Actuated - Threaded
- 125 PSI/8.6 Bar Saturated Steam (TFE Disc) 250 PSI/17.2 Bar Non-Shock Cold Working Pressure - Conforms to MSS SP-80
- Size Range - 3/8" - 2"

26-8715	Lift Check IP	1/2	T-480-Y	10
26-8717	Lift Check IP	1	T-480-Y	10

T-000-D Replacement Waste Cap

26-8940	Waste Cap & Washer	1/8	V01300C	1
---------	--------------------	-----	---------	---

Arrowhead Sill Cock

3/4" ID Swt Inlet, 3/4" Male Hose Outlet. Self-draining with vacuum breaker. Rough Brass Finish

26-9100	Sill Cock	3/4	355SWBFPSD	36
---------	-----------	-----	------------	----