











## MISCELLANEOUS BALL AND GAS VALVES

		Code #	Description	Size	Mfg.#
	Ball Valve with Lever Handle Straight Valve FLARE X FLARE	<b>BrassCraft Gas Ball Valve with Lever Handle.</b> Valve meets ANSI-Z21.15/CGA 9.1 at 1/2 PSI and IAS (AGA/CGA) at 5 PSI. AGA design certified for use with natural, manufactured and mixed gases, as well as liquefied petroleum and LP gas/air mixtures. Corrosion fighting, chrome plated brass ball.			
	Ball Valve with Lever Handle Straight Valve FLARE X FIP	32-0500	Ball Gas Valve Flare x Flare	3/8OD	TBVF-6
		32-0510	Ball Gas Valve Flare x Flare	1/2OD	TBVF-8
		32-0520	Ball Gas Valve Flare x Flare	5/8OD	TBVF-10
	Ball Valve with Lever Handle Straight Valve FIP X FIP	32-0101	Ball Gas Valve	3/8 Flare x 1/2 FIP	TBV6-8
		32-0103	Ball Gas Valve	1/2 Flare x 1/2 FIP	TBV8-8
		32-0110	Ball Gas Valve	FIP x FIP	3/8 TBV-6
		32-0111	Ball Gas Valve	FIP x FIP	1/2 TBV-8
		32-0112	Ball Gas Valve	FIP x FIP	3/4 TBV-12
	601-20CV	<b>Add-A-Line Valve Tee -</b> Add water lines for humidifiers, dishwashers, icemakers, or any new water line. Quality brass ball valve, rated at 150 psi.			
	601-20V	32-0600	5/8" OD Comp Full Slip Tee x 1/4" OD Comp Ball Valve		601-20CV
	601-22VM	32-0650	1/2" Fem Swt Full Slip Tee x 1/4" OD Comp Ball Valve		601-20V
		32-0700	1/2" Fem Swt Full Slip Tee x 1/2" Fem Swt/MIP Ball Valve		601-22VM
<b>Miscellaneous Ball Valves</b>					
<b>Two Way Brass Ball Valves.</b> General purpose valves designed for positive shut-off in either direction. Maximum operating pressure: 500 psi. Maximum operating temperature: 180 deg.F. Plated metal handle, plated brass ball, teflon seat, Buna-N seal.					
	Two Way Valve	445-2240	Ball Valve 1/8 F.N.P.T.		O122F2FBT
		445-2250	Ball Valve 1/4 F.N.P.T.		O274F4FBT
	One Way Valve	<b>One Way Brass Ball Valves.</b> Engineered for economical general purpose use. Single direction flow. Maximum operating pressure: 500 PSI. Maximum operating temperature: 180 deg.F. Plated metal handle, plated brass ball, teflon seat, Buna-N seal.			
		445-2245	Ball Valve 1/4 F.N.P.T.		O254F4FBT
		445-2260	Ball Valve 3/8 F.N.P.T.		O366F6FBT