



# Well Tanks Accessories



80E

Code#	Description	Mfg#
-------	-------------	------

### Check Valve

Enviro-Check® body is cast from an unleaded alloy with threaded female x female connection. Features a non-spin acetal poppet, NITRILE (Buna-N) seal, and stainless steel spring.

Pressure Rating - 400 PSI, Maximum Temperature - 180 deg.F.

380-1800	3/4" enters pipe 1-1/2"	80E
380-1820	1-1/4" enters pipe 2-1/2"	80E



AV

Code#	Description	Mfg#
-------	-------------	------

### Air Valve

380-2020	Air Valve 1/8"	AV
----------	----------------	----



IPG1002

### Pressure Gauge

380-2300	Pressure Gauge 100# 2"	IGP1002
----------	------------------------	---------



FSG-2

Code#	Description	Mfg#
-------	-------------	------

### Pressure Switch

The Class 9013 Type FSG-2 Square D Pumptrol Pressure Switch is the standard water pump switch. It is suitable for all types of pumps: jets, submersibles, reciprocating, etc. 2 pole. Connections are 1/4" FIP threaded.

380-2680	Cut-Out Range 20lbs.-40lbs.	FSG-2
380-2685	Cut-Out Range 30lbs.-50lbs.	FSG-2

